

Dust Buster

A premium surface active agent for dust suppression.

Dust Buster can be used on open rail cars to control loss of coal dust or iron ore to the environment, road surfaces and animal yards. Dust Buster ensures a damp profile for an extended period of time, reducing the constant use of water.

Benefits and uses:

- ✓ Versatile dust suppressant for rail cars, agricultural lime, roadworks etc.
- ✓ One application for extended protection, up to 3 days depending on weather
- ✓ Offers significant reduction in water requirements
- ✓ Will not corrode any equipment
- ✓ Can be applied easily with conventional water spray equipment.
- ✓ Stable under freeze-thaw conditions

TYPICAL ANALYSIS	G/L	W/V %	W/W%	pH	
Surface Active Agent	250	25	21.36	SG	4.2-5.2
Potassium	2.7	0.27	0.23		1.02-1.05
Phosphorus (water soluble P)	1.3	0.13	0.11		

APPLICATION RATES:

0.5-1% per 1000L of water

SAFETY DIRECTIONS:

- Avoid eye contact, extremes of temperature & direct sunlight.
- FIRST AID: If poisoning occurs contact a doctor or Poisons Information Centre Tel 13 11 26. If swallowed DO NOT induce vomiting. Consume a glass of water and seek medical advice. If skin contact occurs remove contaminated clothing and wash skin thoroughly. If eye contact occurs, hold eyes open, flood with water for at least 15 seconds.

PACKAGING
20L, 200L and 1000L

Version Created: 26-Jun-19